



PRODUCT DATA SHEET

EV167-00 Acra-Glo Semi Gloss

General Description: Ever-Gard's Acra-Glo is an interior grade, professional quality, semi-gloss finish paint. Acra-Glo is a professional quality paint and gives contractors a smooth, uniform, decorative semi-gloss finish with high hide to complete jobs efficiently. Acra-Glo is recommended for low abuse interior walls for residential, commercial, and institutional projects.

Available in several stock colors including White Base(00) and is easily tinted to most off-white and pastel colors.

Product Information	
Vehicle Type: Water-Base Vinyl-Acrylic Latex Gloss 20°.....27.5 ± 3.0 60°.....65.0 ± 7.0 85°.....85.0 ± 10.0	Approximate Dry Time at 77°F: To Touch: 30 – 60 min To Recoat: 2 – 4 Hours Dry times affected by Humidity and Temperature
Solids by Weight: 47.8% ± 2% Solids by Volume: 34.3% ± 2%	Recommended Film Thickness: Wet: 4.3 mil Dry: 1.5 mil
Density: 10.45 lbs/gal (White Base) Viscosity: 100 – 105 KU VOC: 48 g/L	Theoretical Coverage: • mil dry: 550 ft ² /gal 1.5 mil dry: 370 ft ² /gal
Storage Temperature: 40°F - 90°F Shelf-Life: 24 Months <small>Some separation may appear. Stir thoroughly before use.</small>	Contrast Ratio 1.5 mil dry: >0.96

Surface Preparation: All surfaces must be clean, dry, and free from dust, dirt, oil, mildew, rust, chalking, loose paint or any other contaminants. New plaster or masonry must be allowed to cure (30 days) before applying. Poured or pre-cast concrete surface should be etched or abraded to increase adhesion and to remove all form release agents. If oil contamination is of concern, use a degreaser. Be aware, degreasers must be rinsed thoroughly and allowed to dry completely.

Repair all cracks, holes, and surface imperfections with a suitable patching material. After filling, patching materials should be sanded down and dusted for loose residue. It is recommended to spot prime after patching holes, cracks, and surface imperfections.

If painting over previously painted surface, test a small area for adhesion prior to completing job. Painting over oil-base paints and other difficult to adhere surfaces require an adhesion promoting primer before painting. If painting over glossy finish, light sanding is needed to achieve necessary adhesion.

Primers: The following systems are recommendations for commonly painted substrates.
 Drywall: EV484 ProSpec PVA Sealer, EV481 Acra Undercoater, EV486 Hi-Hide PVA Sealer
 Wood Substrates: EV477 Total Prep Primer, EV487 Hybrid Wood Primer
 Masonry: EV471 EverBond Concrete Primer, EV472 AcraPoxy Surface Conditioner
 Metal: MB270 DTM Primer, TT7400 Rustless Metal Alkyd Primer
 Difficult to Paint Substrates: EV488 Stik-All Primer Urethane Modified

Application: Apply only when temperature is between 50°F to 90°F and a relative humidity below 80%. Prior to application, thoroughly mix to ensure uniformity. Latex should be spray applied using a tip size of 0.013" to 0.017" at 1500 to 3000 psi. Apply in a uniform manner to minimize blotchiness and sag. Second coat can be applied after 1 hour of dry time. If thinning is desired, add up to 12 fl oz of clean water per gallon of paint.

Clean up: To clean tools, wash with soap and warm water. *In the case of spills*, use containment techniques to prevent further spillage and spreading of material. Wipe up before drying. Dispose of all contaminated materials and containers following federal/state/local regulations.

Environmental: Consult with regulatory and governmental agencies for allowable usage conditions and disposal methods. Do not pour leftover material down the drain.

Safety Measure: Before using, thoroughly Read the Material Safety Data Sheet. Clean hands and contaminated skin with warm water and soap. If irritation develops, wash off immediately with plenty of water.

Limitations: Not recommended for floors, decks, or any surfaces that will be under constant exposure to heavy abrasion, water, or exterior conditions.

Warning! If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.**

To protect yourself and your family, you may contact 1-800-424-LEAD or log on www.epa.gov/lead.

Warning: Do not apply if surface, container or air temperature is below **50 degree F**.

Notice: Purchaser is responsible for legal disposal of containers. Close container after each use. Do not take internally. **Keep out of reach of children. Keep from freezing.**