



PRODUCT DATA SHEET

EV266-00 Perma-Gard

General Description: Ever-Gard's Perma-Gard is an exterior-grade pigmented waterproofing sealer for masonry and wood substrates with a Low Luster finish. Perma-Gard is suitable for both commercial and residential projects where floor-grade waterproofing sealers are required. The Acrylic-Urethane latex is designed for long lasting floor performance with improved resistance against scuffing, marring, and abrasion to protect the substrate. In addition, Perma-Gard is resistant to basic household chemicals as well as strong water resistance. The strong water resistance also affords excellent efflorescent resistance to provide a long lasting color.

Available in White (00), Tint (25), Deep (50), Ultra Deep (75), Neutral (85) Bases. Stock Colors include Ivory, Tile Red, Light Gray, Dark Gray, Mississippi Brown, and more. Consult with your local ShilPark Paint Store for more information.

Product Information – White (266-00)	
Vehicle Type: Water-Base Acrylic Urethane Latex	Approximate Dry Time at 77°F: To Touch: 1 Hour To Recoat: 3 – 4 Hours Dry times affected by Humidity and Temperature
Gloss 20°.....2 - 5 60°.....15 - 20 85°.....30 - 40 LOW LUSTER	
Solids by Weight: 49.5% ± 2%	Recommended Film Thickness: Wet: 2.9 mil Dry: 1.0 mil
Solids by Volume: 35.5% ± 2%	
Density: 11.50 lbs/gal (White Base)	Theoretical Coverage: 1.0 mil dry: 500 - 600 ft ² /gal
Viscosity: 95 – 105 KU	
VOC: < 95 g/L	
Storage Temperature: 40°F - 90°F	Contrast Ratio 1.0 mil dry: >96%
Shelf-Life: 24 Months Some separation may appear. Stir thoroughly before use.	

Surface Preparation: Perma-Gard can be painted directly onto bare concrete, masonry, and wood substrates. Prior to painting all surfaces must be clean, dry, and free from dust, dirt, oil, mildew, rust, chalking, loose paint or any other contaminants. New plaster or masonry must be allowed to cure (30 days) before applying. Poured or pre-cast concrete surface should be etched or abraded to increase adhesion and to remove all form release agents. If oil contamination is of concern, use a degreaser. Be aware, degreasers must be rinsed thoroughly and allowed to dry completely. Repair all cracks, holes, and surface imperfections with a suitable patching material. After filling, patching materials should be sanded down and dusted for loose residue. It is recommended to spot prime after patching holes, cracks, and surface imperfections. If painting over previously painted surface, test a small area for adhesion prior to completing job. Painting over oil-base paints and other difficult to adhere surfaces require an adhesion promoting primer before painting. If painting over glossy finish, light sanding is needed to achieve necessary adhesion.

Primers: The following systems are recommendations for commonly painted substrates.

Metal: MB270 DTM Primer, TT7400 Rustless Metal Alkyd Primer

Difficult to Paint Substrates: EV488 Stik-All Primer Urethane Modified

Manufactured by:



Tibbetts Newport

2337 S Birch St Santa Ana, CA 92707

info@tibbettpaint.com

Application: Stir thoroughly before and during use. Apply only when surface and air temperature is between 50°F to 90°F and a relative humidity below 80%. If applying under severe conditions such as direct sunlight or very dry humidity conditions, additional water or latex extenders may be necessary to account for the shortened open time. Prior to application, thoroughly mix to ensure uniformity. Latex should be spray applied using a tip size of 0.013" to 0.017" at 1500 to 2500 psi. Apply in a uniform manner to minimize blotchiness and sag. Second coat can be applied after 1 hour of dry time. If thinning is desired, add up to 8 fl oz of clean water per gallon of paint.

Caution: All floor coatings may become slippery when wet. If needed, Anti-Slip or Non-Skid Texture such as clean 90 grit sand can be added directly into the paint.

Clean up: To clean tools, wash with soap and warm water. *In the case of spills*, use containment techniques to prevent further spillage and spreading of material. Wipe up before drying. Dispose of all contaminated materials and containers following federal/state/local regulations.

Environmental: Consult with regulatory and governmental agencies for allowable usage conditions and disposal methods. Do not pour leftover material down the drain.

Safety Measure: Before using, thoroughly Read the Material Safety Data Sheet. Clean hands and contaminated skin with warm water and soap. If irritation develops, wash off immediately with plenty of water.

Limitations: Not recommended for floors, decks, or any surfaces that will be under constant exposure to heavy abrasion or water.

Warning! If you scrape sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.**

To protect yourself and your family, you may contact 1-800-424-LEAD or log on www.epa.gov/lead.

Warning: Do not apply if surface, container or air temperature is below **50 degree F**.

Notice: Purchaser is responsible for legal disposal of containers. Close container after each use. Do not take internally. **Keep out of reach of children. Keep from freezing.**

Manufactured by:



Tibbetts Newport

2337 S Birch St Santa Ana, CA 92707

info@tibbettpaint.com